Product advantages mobile crane



Max. lifting capacity: 500 t at 3 m radius Max. height under hook: 145 m with lattice luffing jib Max. radius: 108 m with lattice luffing jib



The variable telescoping **boom** system

- 96 t total weight incl. 50 m telescopic boom and permanent
- outrigger systemBoom change device with hoisting and displacement mechanism on low loader
- Quick Connection for the dismantling of the telescopic boom (10 t axle load)
- Quick Connection for the dismantling of the superstructure (6 t axle load)















Setting on outriggers – quick, convenient and safe

- Permanent supporting pads
- Supporting rams with 500 mm travel
- Automatic levelling of the crane during the supporting 2 x 9° lateral inclination, even with locked suspension
 Inclinometer (electronic display of inclination) with two
- indicators on the carrier and one display on the LICCON monitor
- Indicators of supporting forces on the carrier and on the LICCON monitor
- Control of sliding outriggers with display of the state of extension on the LICCON monitor (optional)





V 500





Robust drive concept

- 4 axles permanently driven (1st, 2nd, 4th and 5th axle)
- 6th axle steered; independent steering of axles 7 and 8
- Automated gear system ZF-TC-TRONIC with converter and retarder, 12 forward and 2 reversed speeds, automated control
- Transfer case
- Driving axles with longitudinal differential locks





Outstanding boom technology

- Focal points of the new boom technology: - oviform boom profile
- patented internal interlocking system of the telescopes
- automatic telescoping system
- Telescopic boom with electronically controlled telescoping system
- Boom bearings of low maintenance polyamide slide blocks
- Outstanding lifting capacities, e.g. 161 t at 10 m radius
 - 161 t at 10 m radius 77 t at 20 m radius 37.4 t at 40 m radius
 - 21.4 t at 60 m radius
 - 13 t at 80 m radius
 - 3.6 t at 108 m radius

- 8-cylinder Liebherr turbo-charged Diesel engine D9508 A7 of 500 kW/680 hp, exhaust emissions acc. to 97/68/EG stage 3 and EPA/CARB Tier 3, energy-saving, emission-optimized, robust and reliable, electronic engine management
- Automated gear system ZF-TC-TRONIC with converter and retarder, 12 forward and 2 reversed speeds, automated control
- Transfer case
- Robust crane axles, welded design
- Max. driving speed 80 km/h
- In addition to the service and parking brakes, the following sustained-action brakes: Exhaust brake with Liebherr auxiliary brake system by valve control, intarder filled to transmission, Telma-type eddy current brake on 4th axle

Weight-optimized steel structure

- Carrier, superstructure and telescopic boom in light-gauge design, calculated by the F.E.M. method, weight-optimized and of particular torsional rigidity
- Tensile property of material with high safety factors through the application of STE 960 (960 N/mm2) for all supporting members

Data bus technique revolutionizes crane electric system

- The data transmission to the individual functional blocks is realized digitally by just a few data cables instead of the traditional electrical wiring. Thus, increased functional reliability and essentially less contacts
- Self-manufactured bus systems, especially adapted to the requirements of a mobile crane
- The vehicle and crane electrics with all cockpit functions, the outrigger system and the boom sensor system are interconnected by 6 Liebherr system busses
- Comprehensive diagnostic facilities, quick localization of errors
- The new data bus technique provides a distinctive increase in functionality and efficiency

Outstanding carrier technology for road and off-road application

- Weight optimized and low maintenance axles of high-tensile steel; perfect track keeping and lateral stability due to special control linkage arrangement
- Steering knuckles mounted on steel bearings, thus bearing failures are practically ruled out
- The perfected and robust axles are manufactured in large series and are part of the trouble-free components of a mobile crane
- The cardan shafts in the axles are maintenance-free and are safely located within the axle body. 70° diagonal toothing enables easy and fast fitting by just a few screws.

Crane and road-preserving Niveaumatik suspension

0

- Maintenance-free suspension rams, free of lateral forces and protected by synthetic tubes
- Level adjustment (suspension set to "travel mode") can be performed automatically by push-button control from any position
- Stable cornering ability due to cross mounting of the hydraulic suspension
- Axle locking system (locking of the suspension for travelling with equipment) integrated into the suspension ram and controllable from the driver's cabin

Crane drive with proved components

- 6-cylinder Liebherr turbo-charged Diesel engine type D936L A6 of 240 kW/326 h.p, exhaust gas emissions in accordance with the directives 97/68/EG stage 3 and EPA/CARB Tier 3, electronically controlled engine speed, engine located laterally to the rear of the superstructure
- Pump distribution gear with 4 servo-controlled axial piston variable displacement pumps operating in a closed oil circuit for winches 1, 2, 3 and slewing gear; 2 servo-controlled double axial piston variable displacement pumps in an open oil circuit for luffing/telescoping; oil cooler within the hydraulic oil circuit



Dismantling of telescopes 2 - 6 or 3 - 6 respectively over the vehicle's rear, front or side



variant 2		
Crane on outriggers, dismantl Minimum counterweight with	ing over the vehicle's fr 2 – 6 telescopes 3 – 6 telescopes	ront 30 t 30 t
(a) e stat		







.



Extend telescopes 2 or 3 to 100 %. Retract telescoping ram and interlock it with telescopes 1 or 2.





Retract telescope 1 or 2 and lower the boom on to the low loader.

Lock the boom to the supporting frame by the lateral pressure plates. Lock the boom head in the supporting device by the ratchet.





Load handling - precise and safe

- 7-section, 84 m long telescopic boom for 84 m height under hook and 74 m radius
- Considerable gain in lifting height and reach due to the exceptionally long boom
- 4-section, 50 m long telescopic boom for 50 m height under hook and 48 m radius
- Oviform boom profile of particular torsional rigidity and for Patented internal interlocking system of the telescopes - of
- High functionality of the boom system due to the automatic telescopic system "Telematik"
- Optimal utilization of the telescopic boom through numerous telescoping variants



84 m

78.6 m

Ä

Multi-variable boom configuration system

- Telescopic boom T, 16.1 m 84 m, also with additional guying system TY and with boom extension TV
 Fixed lattice jib TF, 14 m 63 m, mountable at 0° or 20°, also
- Fixed lattice jib TF, 14 m 63 m, mountable at 0° or 20°, also with additional guying system TYF
 Luffing lattice jib TN, 21 m 91 m, mountable to the 16.1 m
- Luffing lattice jib TN, 21 m 91 m, mountable to the 16.1 m - 78.8 m long telescopic boom at an inclination of 83°, 75° and 67°, also with additional guying system TYN
- and 67°, also with additional guying system TYN
 Intermediate sections of the TF and TN configuration are identical and can be slid into one another for transportation
- Jib A-frames with T-adapter and N-base section form a complete mounting/transport unit and can be mounted with 4 pins only
- Easy-to-rig stay rods which remain on the intermediate sections during transportation
- Standard auxiliary winch for easy reeving of the hoist and luffing ropes
- Rigging of the jib is practicable in suspended condition on restricted sites
- Winch 2 for 2-hook operation or for operation with mast nose
- Winch 3 for luffing of the jib





- The electrical and electronical components are interconnected by the most modern data bus transmission technique
- Self-manufactured bus systems, especially adapted to the requirements of a mobile crane
- Diesel engine and automatic transmission are controlled by a CAN data bus system. The fully electronic drive management reduces fuel consumption and improves the emission of exhaust gases
- The electric systems of the vehicle and crane as well as all cockpit functions, the systems of the outriggers and sensors of the boom are interconnected by 6 Liebherr system busses
- Digital data transmission to the individual functional blocks by only a few data cables instead of the traditional electrical wiring; thus increased functional reliability and essentially less contacts
- The control of the functional blocks is realized by I/O modules, the programming of which is performed by means of the Liebherr system busses. The control intelligence is integrated into the LICCON central units
- Comprehensive diagnostic facilities, guick error localization • The new data bus technique distinctively increases functionality and efficiency



17

88888888

1a

CAN-Bus

Legend	
	LSB Liebherr system bus 1
	LSB Liebherr system bus 2
	LSB Liebherr system bus 3
	LSB Liebherr system bus 4
	LSB Liebherr system bus 5 (also for TN mode
	LSB Liebherr system bus 6 (also for TA mode
	CAN busse
	SCI parialla communication interface

- 6 Control of Allison automatic transmission
- Control of injection pump Liebherr Diesel engine/carrier 8 Slewing sensor slipring unit
- 9 Connection Liebherr system bus (LSB 1, 2, 3, 4, 5, 6)







Comfortable driver's cabin of outstanding functionality

- Modern and comfortable driver's cab of high functionality and convincing design
- Heat and sound absorbing internal panelling
- Ergonomically arranged operating and display elements for safe and convenient handling at permanent operation
- Digital display and keyboard units interconnected with the functional blocks by data bus technique • Air-cushioned driver's and co-driver's seats, headrests, driver's
- seat with pneumatic lumber support
- Height and inclination adjustable steering wheel
- Heated and electrically adjustable rear mirrors •
- Side panes with electrical lifters
- Engine independent auxiliary warm water heater
- · Safety belts for driver and co-driver
- Green-tinted windows for heat absorption
- Automatic windscreen washers/wipers with intermittent control
- Delayed disconnection of interior lighting
- Various racks and boxes for crane documentation, etc.
- Optional equipment Air conditioning, seat heating, 3rd seat with headrest, sleeper berth, cassette radio









Comfortable and spacious crane cabin

- Galvanized crane cab with tinted panes all-round, front knockout window with large parallel windscreen wiper, large skylight of bullet-proof glass with large parallel windscreen wiper, roller blind on skylight, space-saving sliding door, cabin inclinable backwards
- Green tinted front and side panes for heat absorption
- Wash/windscreen wiper for front window and skylight
 2 working projectors, 70 watt each, at the front and rear of
- 2 Working projectors, 70 watt each, at the front and rear o the cabin
- Engine independent additional warm water heater



- Optional equipment
- Air conditioning, seat heating, roller blind on rear pane, cassette radio
- Spring-mounted and hydraulically cushioned crane operator's seat with pneumatic lumber support and headrest
- Convenient armrest-integrated controls, vertically and horizontally adjustable master switch consoles and armrests, ergonomically inclined operating consoles
- Heat and sound absorbing internal panelling
- Display of all essential operating functions on the LICCON monitor

LICCON computer system with practical application programs

• Serial application programs: Safe load indicator, configuration program with configuration image, operating program with operating image, telescoping program with telescoping image, supporting pressure indication, control parameter program, test system; optional extra: work area limitation and LICCON work planner



1		mž st	CODE	>001<	B118	0000	.3(5)
1	62,9	68,1	68,1	73,4	73,4	78,6	84,0
28,8	24.9	28,9	24,3	36.8	24,2	23,6	17,4
22,8	22,9	.d5,6	22,3	24,0	72,4	77,8	16,0
24,8	69,8	- 24,6	3.05	5,55	28,7	29,5	14,8
25,8	18,9	21,3	19,8	28,5	19,2	19,2	13.6
8,85	17.5	1.16	17.6	18.7	17,6	17,8	12,6
38,8	16,1	15,6	15,6	16.1	16.2	15.7	11.5
2.8	14,8		4.	13.9	14,6	14,6	12.5
34,6	15,6	ilit.	1616	11,9	13,4	12,8	- 3.1
K D K					W 3. W		* < *
201311	14	100 1	0.1	000 1	10 1	00.0	
	- 0 + 		07 A	<u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u></u>	40) + 002 +	02 +	200 +
	40 T	2 T	22 T	22 T	32 T	200 T -	200 T
2 1	100 T		92 4	92 +	- <u>7</u> T		200 T
1 3	12 1	AL 1	- m +			102 F	200 4
T 2 16	至+	45 +	2 +	46 +	2 +	<u><u><u></u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u><u></u></u>	100 +
	and the second se		A	10.0 -	5	Lund	
N/	BBn T	-	8.8	10.0 *	63	DOM: N	D K I
\vee		1.20		THPT	338	C 4x	Orly
	-	-					_



LICCON-assisted telescoping system

- Telescoping by single-stage hydraulic ram with hydraulic driving tenons
- Telescoping procedure controllable on the LICCON monitor, convenient and simple guide mode on the monitor, precise approach of the interlocking positions
- Telescopable loads are displayed on the LICCON operating image
- "Automatic operation", fully automatic telescoping to the desired boom length, rapid-cycle system with high working speeds
- Extremely light telescoping system, thus increases in lifting capacity with long booms and at large radii
- Automatic cushioning of telescopes in end positions during telescoping and retracting for preserving the structural members



The LICCON work area limitation system

- It relieves the crane operator, especially in situations where the handling of loads requires his full attention, by controlling the work area limits. Work areas can be restricted by buildings, bridges, roofs, high-tension lines, pipe lines or adjacent cranes. The automatic work area limitation system can easily be programmed and is clearly understandable. Four different limitation functions are practicable:
- Height limitation of the pulley head
- Radius limitation
- Slewing angle limitation
- Limitation of edges







The LICCON test system

- The test system assists the servicing personnel in quickly localizing errors of the sensor system without needing any further measuring instruments
- Convenient interactive functions permit the observation of all in- and outputs of the general system by different displays on the monitor even during crane operation. It equally visualizes the allocation of the individual sensors to the system as well as their function and the terminals concerned in the control cabinet
- The table of contents enables the display of the contents and state of development of the program modules as well as the load charts on the monitor
- The service starts on the monitor, error detection becomes a matter of seconds

The service and diagnostic system LISSy

- This service and diagnostic system LISSy enables the data base-protected control of the programmed errors including error text, description of the cause of error as well as the measures to be taken for the elimination of those errors
- The system provides a quick diagnostic analysis due to the rapid online access to the service documentation such as electric circuit diagrams and workshop manual
- The possibility to memorize the experiences of the crane users in respect to the administrated errors contributes to a progressive growth of the service and diagnostic system LISSy to a data base of experience and knowledge

The LICCON work planner

- The LICCON work planner consists of a software program for planning, simulation and documentation of crane applications on the monitor
- The 2-D planner allows to draw buildings, to write texts and to represent a crane model true to scale including its entire motions within a fictional construction site
- The work planner enables the preparation of more transparent offers, it facilitates the briefing of the crane operators and it can be run on a laptop at the construction site

LICC MLTI-Z	O N TESTSISTEM	- VEPSJON 63.00	LTM 1000/1 NR. 002299900	GRLFFE 8	
(c) LIEBHE	PR-VERK EHO	NGEN 1996	STOP 1 > FF:FF FF.F4.		
SYSTEM MOD	Er	KRAMETRIEB			
SYSTEM-KON TOURATION :			MONITOR :		
	五	AK 1	HAPDWARE 81.88 -	48 k	
FUPPE 0	518	-	FIRMARE 83.15 -	10.97	
20	-	-	antinentin 03-04		
SYSTEM -	EFRON	UHR STSIEN-	EST LSB FOR-	DOE	











Multivariable counterweight system

- Ballast variants of 165 t, 135 t, 105 t, 90 t, 75 t, 45 t, 30 t and 15 t, thus a considerable application spectrum
- · Counterweight slabs of ideal transport dimensions
- The counterweight base slab (15 t) and 6 counterweight slabs (15 t each) as well as the winch frame with winch 2 and 3 can be mounted as a complete unit

Counterweight erection:

- Pile up the counterweight slabs on the carrier frame, the base slab with the ballasting rams forms the carrying plate
- Pick up the winch frame including winch 2, and winch 3 if required, lower it into the fixing devices of the ballasting rams and bolt it
- Pile up the lateral counterweight slabs, depending on the requirement (a total of 4 slabs, 15 t each)
- Connect the hydraulic devices and the remote control panel.
 Extend the ballasting rams and push the winch frame including winches 2 and 3 upwards
- Swing superstructure into the longitudinal axis of the winch frame

- Lower the winch frame by retracting the ballasting rams and enter the centering pins into the location holes of the superstructure. Continue to retract the ballasting rams and raise the counterweight slabs until they sit close to the winch frame
- Disconnect the hydraulic and electric connections

Counterweight frame – compact and quickly mountable

- Modular set-up of the counterweight frame, consisting of base frame and two winch packages, compact transport unit
 Winch 2 and winch 3 with luffing block are pinned and thus quickly interchangeable if required, e.g. for the application of a second LTM 1500-8.1
 The winches are connected to the hydraulic system of the approximate action couplings.
- crane by rapid action couplings
- Auxiliary winch with control panel for reeving of the hoist rope and luffing rope









Electric/electronic crane control with integrated safe load indicator

- Control of the winches, slewing gear as well as of the luffing and telescoping motions by the LICCON system (SPS control)
- Four working motions can be performed independent of one another
- Hoisting/lowering, slewing and luffing speeds are preselectable by 5 steps
- Luffing speed controlled automatically dependent on the boom length
- Very short response rate when initiating the crane motions
- Hoist gear and slewing gear are operating within a "closed oil circuit". This enables a particularly precise hoisting, lowering or slewing of the load. More-over, the potential energy generated during the lowering of a load is not converted into heat but can be re-employed for a 2nd motion. This offers the particular advantage in saving fuel and in a reduced thermal exposure of the oil than in an open circuit. No overheating of the oil.

